

Best Gym Tile - Architectural Specification

Best Gym rubber flooring is an interlocking rubber floor system. The Best Gym rubber flooring system is setting the industry standard for which most high impact weight-room products have been designed around.

Architectural Specifications:

Corners, inside/outside

- 3 Square Feet
- 8.5 Lbs.

Border Tile

- 2 Square Feet
- 6.0 Lbs.

Center tiles

- 4 Square Feet
- 12.0 Lbs.

The Best Gym rubber floor system is the most recognized product worldwide and is known for its easy installation plus minimal maintenance and longevity. The Best Gym rubber flooring system is made from virgin-base rubber and is the most durable USA made all rubber gym-floor on the market.

Features

- Solid vulcanized virgin rubber-base top to bottom, not recycled tire
- Extreme wear resistance
- No adhesive required
- Large 4'x 4' and 2'x 2' tile formats for any configuration
- 10-brilliant colors

Physical Specifications List

• Shore A Durometer 55 at 70 degrees F

- Wet-Dynamic not less than 30
- Tensile Strength not less than 890 psi
- Shrinkage not to exceed 1.1% after 7 days oven aging
- Compression and recovery not less than 90%
- Abrasion Resistance weight loss: grams per revolution 0.0011
- Specific Gravity 1.52
- Percentage Elongation 510%
- Flammability ASTM E-648

Colors - Black, Blue, Tan, Green, Terra Cotta, Burgundy, and Gray